
IBIS/HSPICE Model Quality Report

Design ID: **V89C**

Description: **2Gb DDR3 SDRAM**

Marketing device name(s): **MT41J512M4DA, MT41J256M8DA, MT41J128M16JT, MT41J512M4V89C, MT41J256M8V89C, MT41J128M16V89C**

Valid speed grades: **DDR3-1066, DDR3-1333, DDR3-1600, DDR3-1866, DDR3-2133** ¹

Zip filename: **v89c_ibis.zip**

IBIS filename: **v89c.ibs, v89c_it.ibs** File rev: **2.0**

HSpice filename: **v89c_hspice.zip** File rev: **2.0**

EBD filename (if applicable): File rev:

Die rev: **K**

Date: **February 3, 2012**

Datasheet link: http://www.micron.com/parts/dram/ddr3-sdram/~media/Documents/Products/Data%20Sheet/DRAM/4242Gb_DDR3_SDRAM.ashx

E-mail modelsupport@micron.com for questions regarding Quality Report.

Device Parameters

VDDQ – Slow: **1.425V** Typical: **1.500V** Fast: **1.575V**

VDD – Slow: **1.425V** Typical: **1.500V** Fast: **1.575V**

Junction Temperature (Commercial) - Slow: **110C** Typical: **50C** Fast: **0C**

Junction Temperature (Industrial) - Slow: **110C** Typical: **50C** Fast: **-40C**

VDDQ/VSSQ Decoupling Capacitance: **10.44nF**

Included in HSPICE DQ/DQS models? **Yes** Amount per DQ/DQS model: **522pF/1044pF**

VDDQ/VSSQ Decoupling Capacitance Series Resistance: **~2ohms**

IBIS Quality Summary

1. ☒ Include the IBIS Quality Specification 2.0 Overall IBIS Quality level. For details on IBIS Quality, reference the quality specification and quality checklist on IBIS quality webpage http://www.eda.org/pub/ibis/quality_wip/.

Overall IBIS Quality Level: **IQ3MS**

Exceptions: **N/A**

2. ☒ Include the filename of the IBIS Quality Checklist that accompanies this report.

Filename: **v89c_ibis_quality_checklist.xls**


IBIS MODEL Correlation

Datasheet Correlation


1. ☒ For Output or I/O model compare datasheet IOH/IOL data with IBIS pullup/pulldown data.

a. Model name: **DQ_34_1066**

i. Pulldown I-V versus **JEDEC** specification




ii. Pullup I-V versus **JEDEC** specification




b. Model name: **DQ_40_1066**

i. Pulldown I-V versus **JEDEC** specification



ii. Pullup I-V versus **JEDEC** specification



2. ☒ Compare C_comp with datasheet Input C. Provide C_comp comparison table for all models and for all package combinations (i.e. x4, x8 and x16).³

Component name: **MT41J512M4DA, MT41J256M8DA (78b, x4/x8)**

		IBIS (pF)		Datasheet (pF)	
		min	max	min	max
DQ	C_comp	1.125	1.275	NA	NA
	C package	0.303	0.478	NA	NA
	C_total	1.428	1.753	1.40	2.20
INPUT1	C_comp	0.535	0.685	NA	NA
	C package	0.273	0.368	NA	NA
	C_total	0.808	1.053	0.75	1.30
INPUT2	C_comp	0.585	0.735	NA	NA
	C package	0.223	0.290	NA	NA
	C_total	0.808	1.025	0.75	1.30
CLK	C_comp	0.515	0.665	NA	NA
	C package	0.297	0.302	NA	NA
	C_total	0.812	0.967	0.80	1.30

Component name: **MT41J128M16DA (96b, x16)**

		IBIS (pF)		Datasheet (pF)	
		min	max	min	max
DQ	C_comp	1.125	1.275	NA	NA
	C package	0.254	0.475	NA	NA
	C_total	1.379	1.750	1.40	2.20
INPUT1	C_comp	0.535	0.685	NA	NA
	C package	0.283	0.368	NA	NA
	C_total	0.818	1.053	0.75	1.30
INPUT2	C_comp	0.585	0.735	NA	NA
	C package	0.230	0.334	NA	NA
	C_total	0.815	1.069	0.75	1.30
CLK	C_comp	0.515	0.665	NA	NA
	C package	0.277	0.281	NA	NA
	C_total	0.792	0.946	0.80	1.30

3. ☒ If slew rate specifications (rise/fall slew) are available from the datasheet, complete HSpice simulations to generate slew rate data and provide a comparison table.⁴

Model	Slew Rate (V/ns)	IBIS			Datasheet	
		min	typ	max	min	max
DQ_34_1066	Rising	2.13	3.28	4.68	2.50	6.00
	Falling	1.97	2.96	4.03	2.50	6.00
DQ_40_1066	Rising	2.13	3.36	4.73	2.50	6.00
	Falling	2.03	3.18	4.25	2.50	6.00
DQ_34_1600	Rising	2.32	3.39	4.74	2.50	6.00
	Falling	2.06	3.01	4.02	2.50	6.00
DQ_40_1600	Rising	2.26	3.43	4.72	2.50	6.00
	Falling	2.37	3.20	4.21	2.50	6.00
DQ_34_1866	Rising	2.83	3.51	4.80	2.50	6.00
	Falling	2.13	3.05	4.06	2.50	6.00
DQ_40_1866	Rising	2.74	3.51	4.78	2.50	6.00
	Falling	2.51	3.23	4.25	2.50	6.00

4. ☒ Compare ODT data with datasheet.

ODT calculated using the formula $RTT = (V_{IH(ac)} - V_{IL(ac)}) / (I(V_{IH(ac)}) - I(V_{IL(ac)}))$

ODT20	TYP	MIN	MAX
Vil (V)	0.575	0.5375	0.6125
Vih (V)	0.925	0.8875	0.9625
Ivil (A)	-7.49E-03	-6.65E-03	-7.77E-03
Ivih (A)	8.68E-03	7.51E-03	9.92E-03
	TYP	MAX	MIN
Rtt (Model)	21.63	24.72	19.79
Rtt (datasheet-in units of ZQ/12)	1.0	1.6	0.9
Rtt (datasheet)	20	32	18

ODT30	TYP	MIN	MAX
Vil (V)	0.575	0.5375	0.6125
Vih (V)	0.925	0.8875	0.9625
Ivil (A)	-5.00E-03	-4.43E-03	-5.18E-03
Ivih (A)	5.79E-03	5.01E-03	6.61E-03
	TYP	MAX	MIN
Rtt (Model)	32.45	37.07	29.69
Rtt (datasheet-in units of ZQ/12)	1.0	1.6	0.9
Rtt (datasheet)	30	48	27

ODT40	TYP	MIN	MAX
Vil (V)	0.575	0.5375	0.6125
Vih (V)	0.925	0.8875	0.9625
Ivil (A)	-3.75E-03	-3.33E-03	-3.89E-03
Ivih (A)	4.34E-03	3.75E-03	4.96E-03
	TYP	MAX	MIN
Rtt (Model)	43.25	49.43	39.57
Rtt (datasheet-in units of ZQ/12)	1.0	1.6	0.9
Rtt (datasheet)	40	64	36

ODT60	TYP	MIN	MAX
Vil (V)	0.575	0.5375	0.6125
Vih (V)	0.925	0.8875	0.9625
Ivil (A)	-2.50E-03	-2.22E-03	-2.59E-03
Ivih (A)	2.90E-03	2.50E-03	3.31E-03
	TYP	MAX	MIN
Rtt (Model)	64.86	74.12	59.34
Rtt (datasheet-in units of ZQ/12)	1.0	1.6	0.9
Rtt (datasheet)	60	96	54


ODT120	TYP	MIN	MAX
Vil (V)	0.575	0.5375	0.6125
Vih (V)	0.925	0.8875	0.9625
Ivil (A)	-1.25E-03	-1.11E-03	-1.30E-03
Ivih (A)	1.45E-03	1.25E-03	1.65E-03
	TYP	MAX	MIN
Rtt (Model)	129.71	148.23	118.66
Rtt (datasheet-in units of ZQ/12)	1.0	1.6	0.9
Rtt (datasheet)	120	192	108

Measurement Correlation


1. ☒ For Output or I/O models compare measured IOH/IOL data with IBIS pullup/pulldown data. If the measurement conditions are different than the IBIS conditions, run HSpice simulations using the same measurement conditions such as VCC, temperature, and process. Include measurement conditions in the pullup/pulldown images.

a. Model name: **DQ_34_1066**

i. Pulldown I-V versus Measurement




ii. Pullup I-V versus Measurement




b. Model name: **DQ_40_1066**

i. Pulldown I-V versus Measurement



ii. Pullup I-V versus Measurement



2. ☒ Compare C_comp with measured C_comp. Provide C_comp comparison table for all models and for all package combinations (i.e x4, x8 and x16).

Component name: **MT41J512M4DA, MT41J256M8DA (78b, x4/x8)**

		IBIS (pF)			Measured (pF)		
		min	typ	max	min	typ	max
DQ	C_comp	1.125	1.200	1.275	NA	NA	NA
	C package	0.303	0.378	0.478	NA	NA	NA
	C_total	1.428	1.578	1.753	1.510	1.566	1.650
INPUT1	C_comp	0.535	0.610	0.685	NA	NA	NA
	C package	0.273	0.327	0.368	NA	NA	NA
	C_total	0.808	0.937	1.053	0.900	0.940	0.970
INPUT2	C_comp	0.585	0.660	0.735	NA	NA	NA
	C package	0.223	0.255	0.290	NA	NA	NA
	C_total	0.808	0.915	1.025	0.870	0.913	0.960
CLK	C_comp	0.515	0.590	0.665	NA	NA	NA
	C package	0.297	0.299	0.302	NA	NA	NA
	C_total	0.812	0.889	0.967	0.880	0.885	0.890

Component name: **MT41J128M16DA (96b, x16)**

		IBIS (pF)			Measured (pF)		
		min	typ	max	min	typ	max
DQ	C_comp	1.125	1.200	1.275	NA	NA	NA
	C package	0.254	0.330	0.475	NA	NA	NA
	C_total	1.379	1.530	1.750	1.430	1.528	1.670
INPUT1	C_comp	0.535	0.610	0.685	NA	NA	NA
	C package	0.283	0.337	0.368	NA	NA	NA
	C_total	0.818	0.947	1.053	0.890	0.963	1.040
INPUT2	C_comp	0.585	0.660	0.735	NA	NA	NA
	C package	0.230	0.284	0.334	NA	NA	NA
	C_total	0.815	0.944	1.069	0.890	0.983	1.090
CLK	C_comp	0.515	0.590	0.665	NA	NA	NA
	C package	0.277	0.279	0.281	NA	NA	NA
	C_total	0.792	0.869	0.946	0.870	0.880	0.900

3. ☐ If measured clamp current data is available provide an IBIS and measurement comparison for all models.

Not Available


4. ☐ If slew rate data (rise/fall slew) is available from measurements, complete HSpice simulations to generate slew rate data and provide a comparison table.

Not Available


IBIS vs HSPICE Correlation

1. ☒ For all Output or I/O models, run HSpice transient simulations using encrypted netlists and the IBIS model (b-element).
 - a. ☒ Use the setup and node naming conventions shown below for the IBIS and HSpice deck file (.sp file). Update the setup diagram if it is different. Indicate the version of HSPICE simulator used for simulations: **2008.09**
 - b. ☒ Run simulations for all corners cases and at maximum allowable speed grade


i. DQ_34_1600 driving DQ_34_1600




ii. DQ_34_1600 driving DQ_34_ODT20_1600




iii. DQ_34_1600 driving DQ_34_ODT30_1600




iv. DQ_34_1600 driving DQ_34_ODT40_1600




v. DQ_34_1600 driving DQ_34_ODT60_1600




vi. **DQ_34_1600 driving DQ_34_ODT120_1600**




vii. **DQ_40_1600 driving DQ_40_ODT60_1600**




viii. DQ_34_1866 driving DQ_34_1866




ix. DQ_34_1866 driving DQ_34_ODT20_1866




X. DQ_34_1866 driving DQ_34_ODT30_1866




xi. DQ_34_1866 driving DQ_34_ODT40_1866




xii. **DQ_34_1866 driving DQ_34_ODT60_1866**




xiii. **DQ_34_1866 driving DQ_34_ODT120_1866**




xiv. **DQ_40_1866 driving DQ_40_ODT60_1866**




xv. **DQ_34_2133 driving DQ_34_2133**




xvi. **DQ_34_2133 driving DQ_34_ODT20_2133**




xvii. **DQ_34_2133 driving DQ_34_ODT30_2133**




xviii. **DQ_34_2133 driving DQ_34_ODT40_2133**




xix. **DQ_34_2133 driving DQ_34_ODT60_2133**




XX. DQ_34_2133 driving DQ_34_ODT120_2133



xxi. DQ_40_2133 driving DQ_40_ODT60_2133



Setup



Comments:

1. IBIS model may not reflect speed grade availability.
2. IBIS Version is 4.2.
3. C_comp is compared with the DDR3-1866 specification only.
4. Slew rate is based on HSPICE simulation with a 25ohm load to Vtt. This includes simple package parasitics.
5. INPUT1_* is applicable to: A3, A4, A5, A6, A7, A8, A9, A13, A14, CKE, CS#, ODT
INPUT2_* is applicable to: A0, A1, A2, A10, A11, A12, BA0, BA1, BA2, CAS#, RAS#, WE#

Document Revision History

Rev **1.0** - Date **7/22/2011**

- a. IBIS revision **1.0**
- b. HSpice revision **1.0**

Rev **2.0** - Date **2/03/2012**

- a. IBIS revision **2.0**
- b. HSpice revision **2.0**